



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2001050034 A**(43) Date of publication of application: **23.02.01**

(51) Int. Cl. **F01N 3/08**
F01N 3/20
F01N 3/28
F01N 3/36
F02M 25/07

(21) Application number: **11219617**(22) Date of filing: **03.08.99**(71) Applicant: **HINO MOTORS LTD**

(72) Inventor: **SATO SHINYA**
HOSOYA MITSURU
SHIMODA MASATOSHI

(54) **EXHAUST EMISSION CONTROL METHOD FOR
 DIESEL ENGINE**

reduction catalyst 5.

COPYRIGHT: (C)2001,JPO

(57) Abstract:

PROBLEM TO BE SOLVED: To achieve a practical use of an emission exhaust gas purification device in which by control NOx is released actively from a NOx storage compound according to a reactive temperature range of a NOx reduction catalyst, and the NOx storage compound is compatibly used as the NOx reduction catalyst.

SOLUTION: NOx in exhaust gas 2 is oxidized and stored as nitrate temporarily by a NOx storage compound 4. By adding at least one kind among H₂, CO, and HC to the exhaust gas 2, while an engine is operated with a necessarily reduced intake air amount to be leaner than a stoichiometric air-fuel ratio, NOx is decomposed and released from the NOx storage compound 4 so as to regenerate the NOx storage compound 4. The released NOx is reduced and purified through being reacted with at least one kind among H₂, CO, and HC on a NOx

